



# MOTO FORMULA 2T

## ■ Description

---

**REPSOL MOTO FORMULA 2T** is modern, high quality two-stroke motorcycle oil specially designed for two-stroke motorcycles which required all round protection. It is formulated from highly refined base oils fortified with specially selected additives to provide excellent performance and lubrication for engines which operating at extreme conditions. It is recommended for use in air and water cooled two-stroke motorcycle engines.

## ■ Properties

---

- Provide high level engine cleanliness, minimizes the formation of deposits.
- Excellent lubrication at all driving conditions.
- Protect engine parts from excessive wear, extending the engine's life.
- Prevent spark plug sweating and prevents the piston rings from sticking.

## ■ Quality levels

---

- API TA

## ■ Technical Characteristics

---

	UNIT	METHOD	VALUE
Density @ 15°C	g/cm <sup>3</sup>	ASTM D 4052	0.887
Viscosity @ 100°C	cSt	ASTM D 445	8.8
Viscosity @ 40°C	cSt	ASTM D 445	68.0
Viscosity index	-	ASTM D 2270	102
Flash point, open cup	°C	ASTM D 92	200 min
Pour point	°C	ASTM D 97	-6 max

## ■ Hazard Identification

---

This product is not classified as toxic or hazardous under current legislation.

## ■ Handling

---

Minimum precautions should be taken to avoid prolonged contact with the skin. The use of gloves, visors or glasses is recommended to avoid splashes.

## ■ Health and safety hazards

---

**Inhalation:** Given that it is not a particularly volatile product, the risk of inhalation is minimal.

**Ingestion:** Do not induce vomiting. Supply water. Seek medical advice.

**Contact with the skin:** Wash thoroughly with soap and water.

**Eyes:** Wash thoroughly with water.

**General measures:** Seek medical advice.

## ■ Fire-extinguishing measures

---

No special measures required.

**Fire-extinguishing measures:** Foams, dry chemicals, CO<sub>2</sub>, water spray. Do not apply the jet of water directly as this could cause the product to disperse.

## ■ Environmental precautions

---

Risk of physical contamination when spilled (waterways, coastal areas, soils, etc.) due to its floatability and oily consistency; could cause harm to flora and fauna on contact. Avoid material getting into water outlets.

**Decontamination and cleaning:** Treat as an accidental oil spillage. Prevent dispersion using mechanical barriers and remove by physical or chemical means.

A safety information file is available on request.

This PDS is available at [www.repsoloil.com.my](http://www.repsoloil.com.my).

For more information about Repsol please visit [www.repsol.com](http://www.repsol.com)

Unless otherwise indicated, the figures cited in technical characteristics should be considered typical.