

MOTO FORMULA 4T SAE 40



MOTORCYCLE

Lubricants

Description

REPSOL MOTO FORMULA 4T SAE 40 is a mineral and mono-grade four-stroke motorcycle oil which specially designed to provide reliable lubrication and engine protection for four-stroke motorcycles. Its formulation protects engine against wear and deposits throughout the oil change period. This motorcycle oil is recommended for use in most of the types of four-stroke motorcycle engines and some gearboxes in two-stroke motorcycles.

Properties

- Enhanced wear and deposits control at critical components.
- Special formulation to maintain oil viscosity in all riding conditions.
- Provide excellent lubrication and engine protection.
- Provide smooth clutch and gearbox operation.

Quality levels

- API SG

Technical characteristics

	UNIT	METHOD	VALUE
SAE grade			40
Density at 15°C	g/cm ³	ASTM D 4052	0.893
Viscosity at 100°C	cSt	ASTM D 445	14.0
Viscosity at 40°C	cSt	ASTM D 445	138.0
Viscosity index	-	ASTM D 2270	98
Flash point, open cup	°C	ASTM D 92	210 min.
Pour point	°C	ASTM D 97	-6 max.
T.B.N	mg KOH/g	ASTM D 2896	6.1

A safety data file is available on request.

This PDS is available at www.repsol.com.my.
For more information about Repsol please visit www.repsol.com.

repsol.com
+34 901 111 999

Technical data sheet. Review 2. March 2016.