

ELITE FORMULA TECH 10W30



AUTOMOTIVE

Lubricants

Description

REPSOL ELITE FORMULA TECH 10W30 is formulated with highly refined base oils incorporated with latest additive system to provide outstanding wear protection, engine cleanliness and also reduced friction, which could help in contributing greater fuel efficiency performance to the engines running under the most demanding driving conditions. It is recommended for use in all types of gasoline vehicles that required API SN or earlier specification 10W30 lubricant.

Properties

- Optimize engine's performance in all driving conditions.
- Minimize friction to provide greater fuel efficiency.
- Maintain engine cleanliness throughout the oil drain intervals.
- Excellent anti-wear properties to extend critical component's life span.
- Provide fast lubrication during engine start up.

Quality levels

- API SN
- ILSAC GF-5

Technical characteristics

	UNIT	METHOD	VALUE
SAE grade			10W30
Density at 15°C	g/cm ³	ASTM D 4052	0.854
Viscosity at 100°C	cSt	ASTM D 445	11.0
Viscosity at 40°C	cSt	ASTM D 445	69.0
Viscosity at -25°C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	151
Flash point, open cup	°C	ASTM D 92	210 min.
Pour point	°C	ASTM D 97	-27 max.
T.B.N.	mg KOH/g	ASTM D 2896	7.6

A safety data file is available on request.

This PDS is available at www.repsol.com.my.
For more information about Repsol please visit www.repsol.com.

repsol.com
+34 901 111 999

Technical data sheet. Review 1. April 2016.