

ELITE FORMULA TECH 10W40



AUTOMOTIVE

Lubricants

Description

REPSOL ELITE FORMULA TECH 10W40 has been blended based on highly refined base oils fortified with latest additives technology which enable it meets the most stringent industry requirements. Its advanced formulation helps to protect the engines against the formation of deposits and sludge whilst offering the maximum engine's performance throughout the oil drain intervals. It is recommended for use in all types of gasoline vehicles that required API SN or earlier specification 10W40 lubricant.

Properties

- Maintain engine's performance in all driving conditions.
- Protect engines against harmful deposits and sludge.
- Excellent thermal and oxidation resistance reducing oil ageing throughout the oil drain intervals.
- Excellent anti-wear properties to extend critical component's life span.
- Very good shear resistance to retain viscosity at high temperature and high stress.

Quality levels

- API SN

Technical characteristics

	UNIT	METHOD	VALUE
SAE grade			10W40
Density at 15°C	g/cm ³	ASTM D 4052	0.856
Viscosity at 100°C	cSt	ASTM D 445	14.2
Viscosity at 40°C	cSt	ASTM D 445	100.0
Viscosity at -25°C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	145
Flash point, open cup	°C	ASTM D 92	210 min.
Pour point	°C	ASTM D 97	-27 max.
T.B.N.	mg KOH/g	ASTM D 2896	7.6

A safety data file is available on request.

This PDS is available at www.repsol.com.my.
For more information about Repsol please visit www.repsol.com.

repsol.com
+34 901 111 999

Technical data sheet. Review 1. April 2016.