

MOTO FORMULA 4T 10W40



MOTORCYCLE

Lubricants

Description

REPSOL MOTO FORMULA 4T 10W40 is a mineral four-stroke motorcycle oil specially recommended for modern and high performance motorcycles. The formulation is fortified with the latest additives technology which makes it suitable for engines running in extreme and stressful conditions that required reliable performance and protection in all riding conditions.

Properties

- High performance multi-grade oil with excellent thermal and shear stability that provides reliable engine performance under extreme conditions.
- Outstanding wear protection for longer service life of gear and clutch system.
- Excellent oxidation stability and cleanliness to prevent formation of sludge and deposits.

Quality levels

- API SM
- JASO T 903:2016 MA

Technical characteristics

	UNIT	METHOD	VALUE
SAE grade			10W40
Density at 15°C	g/cm ³	ASTM D 4052	0.868
Viscosity at 100°C	cSt	ASTM D 445	14.5
Viscosity at 40°C	cSt	ASTM D 445	100.0
Viscosity at -25°C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	150
Flash point, open cup	°C	ASTM D 92	200 min.
Pour point	°C	ASTM D 97	-27 max.
T.B.N.	mg KOH/g	ASTM D 2896	7.1

A safety data file is available on request.

This PDS is available at www.repsol.com.my.
For more information about Repsol please visit www.repsol.com.

repsol.com
+34 901 111 999

Technical data sheet. Review 3. January 2019.