

MOTO FORMULA PREMIUM 4T 10W40



MOTORCYCLE

Lubricants

Description

REPSOL MOTO FORMULA PREMIUM 4T 10W40 is a semi-synthetic motorcycle oil formulated with a perfect combination of base oils and an advanced additive technology. Specially recommended for high performance motorcycle engines, it provides first-time response to the rider and helps the motorcycle performs at its peak level under varying riding conditions.

Properties

- High performance multi-grade oil formulated with advanced anti-wear additives to deliver total protection to the engine.
- Excellent thermal and shear resistance to encourage rapid oil flow and fuel efficiency performance.
- Enhanced smoother clutch and gearbox operations.
- Excellent lubrication at high and low operating temperature.

Quality levels

- API SM
- JASO T 903:2016 MA

Technical characteristics

	UNIT	METHOD	VALUE
SAE grade			10W40
Density at 15°C	g/cm ³	ASTM D 4052	0.864
Viscosity at 100°C	cSt	ASTM D 445	14.5
Viscosity at 40°C	cSt	ASTM D 445	96.0
Viscosity at -25°C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	157
Flash point, open cup	°C	ASTM D 92	200 min.
Pour point	°C	ASTM D 97	-27 max.
T.B.N.	mg KOH/g	ASTM D 2896	7.1

A safety data file is available on request.

This PDS is available at www.repsol.com.my.
For more information about Repsol please visit www.repsol.com.

repsol.com
+34 901 111 999

Technical data sheet. Review 3. January 2019.