

# MOTO FORMULA 4T 15W50



MOTORCYCLE

Lubricants

## Description

**REPSOL MOTO FORMULA 4T 15W50** is a mineral four-stroke motorcycle oil suitable for engines running in extreme and long distance driving conditions. It is specially recommended for engines that require reliable performance and protection under all riding conditions. The formulation is fortified with the latest additives technology to protect the engine and maintain its responsiveness.

## Properties

- Provides reliable engine performance under extreme conditions.
- Suitable for use in old and modern high performance motorcycles.
- Outstanding wear protection for longer service life of gear and clutch system.
- Excellent oxidation stability and cleanliness to prevent formation of sludge and deposits.
- Outstanding shear stability to keep the oil viscosity in grade.

## Quality levels

- API SM
- JASO T 903:2016 MA

## Technical characteristics

	UNIT	METHOD	VALUE
SAE grade			15W50
Density at 15°C	g/cm <sup>3</sup>	ASTM D 4052	0.875
Viscosity at 100°C	cSt	ASTM D 445	17.5
Viscosity at 40°C	cSt	ASTM D 445	135.0
Viscosity at -20°C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	140
Flash point, open cup	°C	ASTM D 92	200 min.
Pour point	°C	ASTM D 97	-27 max.
T.B.N.	mg KOH/g	ASTM D 2896	7.1

A safety data file is available on request.

This PDS is available at [www.repsol.com.my](http://www.repsol.com.my).  
For more information about Repsol please visit [www.repsol.com](http://www.repsol.com).

[repsol.com](http://repsol.com)  
+34 901 111 999

Technical data sheet. Review 3. January 2019.