

Description

Lubricant oil for general use in 2-stroke engines. It is suitable for a wide range of motorcycles and is mainly recommended for urban use. It is a clean oil, which cares for the engine and always keeps the exhaust vents clean. In addition, it supports very high temperatures produced by intensive use in city traffic, or as a consequence of carrying a passenger on a scooter or a small cylinder capacity motorcycle.

Properties

- Increased lubricating power that reduces wear, extending the engine's life span.
- Minimizes the formation of deposits, keeping the exhaust ports clean.
- Reduces spark plug sweating and prevents the piston rings from sticking.
- Also suitable for lawnmowers, chainsaws and other equipment used for DIY or small-scale agriculture.
- Perfumed

Quality levels

- JASO M345 FB
- API TC

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm ³	ASTM D 4052	0.8821
Viscosity at 100 °C	cSt	ASTM D 445	8.9
Viscosity at 40 °C	cSt	ASTM D 445	65
Viscosity index	-	ASTM D 2270	110
Flash point, open cup	°C	ASTM D 92	146
Pour point	°C	ASTM D 97	-12 max.
T. B. N.	mg KOH/g	ASTM D 2896	1.6
Sulphated ash	% weight	ASTM D 874	0.1

The above mentioned characteristics are typical values and should not be considered product specifications

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. March 2018.